

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 166 929 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
02.01.2002 Bulletin 2002/01

(51) Int Cl.7: **B23B 27/00**, **B23B 51/00**,
B23C 5/00

(21) Application number: **00118946.3**

(22) Date of filing: **01.09.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

- **Fukumura, Naoe**
Chikusa-ku Nagoya-shi Aichi-ken (JP)
- **Mizukado, Masayoshi**
Gifu-ken (JP)
- **Kikata, Kazuhiro**
Gifu-ken (JP)
- **Miyazaki, Sadami**
Aichi-ken (JP)
- **Maki, Koichi**
Aichi-ken (JP)

(30) Priority: **29.06.2000 JP 2000196146**

(71) Applicant: **YAMAZAKI MAZAK KABUSHIKI**
KAISHA
Oguchi-Cho Niwa-Gun Aichi-Ken (JP)

(72) Inventors:
• **Yamazaki, Tsunehiko**
Nagoya-shi Aichi-ken (JP)


(74) Representative: **Bauer, Wulf, Dr.**
Bayenthalgürtel 15
50968 Köln (Marienburg) (DE)

(54) **Combination tool**

(57) In a complex tool 1 to be used by attachably and detachably installing on a tool holding means, a main body 3 is provided, a tool means for turning 13 is provided with an outer peripheral portion of the main body, a projected rotating tool means 10 is provided, corresponding the axial center CT1 of the projected rotating tool means and the axial center CT of the main body with each other so as to selectively perform turning

machining with the tool means for turning 13 or rotating machining for machining on a workpiece 15 by rotating the projected rotating tool means. Both machinings, turning machining and rotating machining with a drill (a tap) are possible with one tool by the tool means for turning 13 and the projected rotating tool means 10, so the present invention can be applied to recent advanced machining and its machining efficiency can be increased.

FIG. 1



Description

BACKGROUND OF THE INVENTION

[0001] This invention relates to a complex tool capable of both machining, turning machining where a tool is fixed and held at the time of machining and drilling (tapping), milling and end mill machining where a tool is rotated at the time of machining.

[0002] A known conventional complex tool is one installing a plurality of inserts at the top end of a tool itself in the shape of a bar. Using such a complex tool, milling machining is performed on the workpiece surface in a fixed state by the insert of the top end by rotating the complex tool according to machining contents, and turning machining is performed by the insert of the top end by rotating a workpiece in such a state that the complex tool is fixed and held.

[0003] In recent years, the machining to be performed with a machine tool, such as turning machining, trends to become complex and advanced. The development of the tool capable of both machining, turning and drilling (tapping) (the only "drill" in the present specification includes "tap") with one tool is expected in addition to the complex tool above-mentioned.

[0004] The object of the present invention is to provide a complex tool capable of performing both machining, turning machining and rotating machining by a drill (a tap), a milling cutter and an end mill with one tool, taking the above-mentioned circumstances into consideration.

SUMMARY OF THE INVENTION

[0005] The invention of claim 1 is a complex tool to be used by attachably and detachably installing on a tool holding means, comprising:

- a main body;
 - a tool means for turning provided at an outer periphery portion of said main body; and
 - a projected rotating tool means provided so as to correspond an axial center of said projected rotating tool means with an axial center of said main body; said complex tool having further character:
- selectively performing turning machining with said tool means for turning or rotating machining for machining on a workpiece by rotating said projected rotating tool means.

[0006] According to the invention of claim 1, both machinings, turning machining and rotating machining with a drill (a tap) are possible with one tool by the tool means for turning and the projected rotating tool means, so the present invention can be applied to recent advanced machining and its machining efficiency can be increased.

[0007] The invention of claim 2 is the complex tool wherein said projected rotating tool means is fixedly pro-

vided in the axial center direction of said main body with respect to said main body.

[0008] According to the invention of claim 2, the complex tool can be comprised with simple structure.

[0009] The invention of claim 3 is the complex tool wherein said projected rotating tool means is provided so as to move in the axial center direction of said main body with respect to said main body.

[0010] According to the invention of claim 3, the projected rotating tool means can be moved in the axial center direction. Then, the projected rotating tool means can be retracted to the position where it does not obstruct the machining at the time of machining with the tool means for turning, and turning machining can be smoothly performed.

[0011] The invention of claim 4 is the complex tool as set forth in the invention of claim 3 wherein a movement driving means of said projected rotating tool means is provided with the main body, and said movement driving means moves and drives said projected rotating tool means in the axial center direction by driving fluid supplied from said tool holding means side.

[0012] According to the invention of claim 4, the projected rotating tool means can be driven from the tool holding means side, then, the structure of the complex tool can be made simple.

[0013] The invention of claim 5 is the complex tool wherein said projected rotating tool means is a drill, a tap, a milling cutter or an end mill.

[0014] According to the invention of claim 5, various kinds of rotating tools can be used, then, various kinds of machining is possible.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Fig.1 is a view showing an example of a complex tool to which the present invention is applied.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0016] A complex tool 1 has a tool holder 2, as shown in Fig. 1. The tool holder 2 has a main body 3 cylindrically formed as a whole. On the right hand of the figure of the main body 3, a tool holding slot 5 for exchanging an automatic tool is formed in the shape of a ring. On the right hand of the figure of the tool holding slot 5, a shank 6 is formed in the shape of a taper.

[0017] A hole 3a is provided with the main body 3 so as to penetrate in the direction of axial center CT of the main body 3. The hole 3a is comprised of an operating oil supply portion 3b on the right hand of the figure, which diameter is D1, a tool holding body storing cylinder 3c coaxially formed on the left hand of the operating oil supply portion 3b, which diameter is D2 smaller than D1, and a guide portion 3d coaxially formed on the left hand of the tool holding body storing cylinder 3c, which diameter is D3 further smaller than D2.

[0018] A slidable holder 7 is inserted into the tool hold-

ing body storing cylinder 3c, being free to slide in the direction of the axial center CT of the complex tool 1, that is, in the direction as shown by the arrows A and B. On the right edge portion of the figure of the slidable holder 7, a slidable contacting portion 7a in the shape of a circular ring is formed being free to slide in the direction as shown by the arrows A and B on the wall face of the tool holding body storing cylinder 3c. Between the slidable contacting portion 7a of the slidable holder 7 and a side wall 3e of the tool holding body storing cylinder 3c, a coiled spring 9 is provided so as to shrink, covering the periphery of the slidable holder 7. The slidable holder 7 is always energized by the coiled spring 9 in the direction as shown by the arrow B.

[0019] On the top end portion of the slidable holder 7, a tool installation portion 7b inserted into the guide portion 3d is formed. A tool storing hole 7c is provided with the tool installation portion 7b in the axial center CT direction of the complex tool 1. The top end of the tool storing hole 7c is open for the top end portion of the slidable holder 7, that is, for the top end portion of the tool holder 2. A projected rotating tool 10, which is a tool for machining a workpiece by rotating itself, such as a drill (including a tap, as mentioned before), a milling cutter and an end mill, is attachably and detachably installed on the tool storing hole 7c through fixed screws 11, 11. The axial center CT1 of the projected rotating tool 10 corresponds with the axial center CT of the main body 3 of the tool holder 2, that is, the rotational center of the tool holder 2.

[0020] On the outer peripheral portion of the tool installation portion 7b, a key seat 7d is formed in the direction as shown by the arrows A and B. A key 12 engaged with the main body 3 is provided with the key seat 7d such that its top end portion is inserted and engaged.

[0021] Besides, a cutting tool storing slot 3f is formed on the outer peripheral portion of the main body 3 so as to penetrate. On the cutting tool storing slot 3f, a cutting tool 13, which is a known turning tool, is attachably and detachably installed by an attaching bolt (not shown). An insert 13a is installed on the top end portion of the cutting tool 13 such that a top end 13b of the insert 13a is projected outside predetermined quantity X1 with respect to an outer peripheral face 3g of the main body 3 (upper hand in the figure). Furthermore, the top end 13b of the insert 13a is installed so as to project predetermined quantity X2 on the left hand in the figure with respect to a top end portion 3h of the left hand of the figure of the main body 3.

[0022] The complex tool 1 has the above-mentioned structure. Then, in order to perform turning machining with the complex tool 1, the complex tool 1 is installed on the tool holding means, such as a tool rest of a machine tool (not shown) through the shank 6. The tool holding means can fix and hold the complex tool 1 at a predetermined angle position around the axial center CT, as well as can rotate and drive the complex tool 1 around the axial center CT. Then, in order to perform the

turning machining with the complex tool 1, the complex tool 1 is held and fixed at a predetermined angle position around the axial center CT such that the insert 13a of the cutting tool 13 of the complex tool 1 is faced to the cutting portion of a workpiece 15 on which turning machining is performed. In such a state, the machining is performed by moving and driving the cutting tool 13 of the complex tool 1 with respect to the workpiece 15 being in a rotating state in the direction as shown by the arrows A and B, and in the direction as shown by the arrows C and D so as to contact the top end 13b of the insert 13a with the workpiece 15.

[0023] On this occasion, the slidable holder 7, on which the projected rotating tool 10 is installed, is positioned at a retracted position, moved in the arrow B direction by the elasticity of the coiled spring 9, and a top end 10a of the projected rotating tool 10 is retracted at a retracted position RP, projecting predetermined quantity $X3 < X2$ on the left hand in the figure rather than the top end portion 3h of the left hand of the figure of the main body 3. In this state, the top end 10a of the projected rotating tool 10 is positioned at the position retracted on the right hand in the figure rather than the top end 13b of the cutting tool 13 for turning. Then, the machining is smoothly executed by the cutting tool 13 without hindrance by the projected rotating tool 10 at the time of turning machining with the cutting tool 13.

[0024] Subsequently, in order to form a hole and a screw on an end face 15a of the workpiece 15 with the projected rotating tool 10, operating oil 16, such as coolant, is supplied from the operating oil supply portion 3b of the main body 3 through the tool rest on which the complex tool 1 is installed. Then, the slidable holder 7 is pressed and moved in the direction as shown by the arrow A against the elasticity of the coiled spring 9 by the operating oil 16 supplied operating oil supply portion 3b, and the projected rotating tool 10 installed on the slidable holder 7 is also moved and driven in the direction as shown by the arrow A, restricting the rotation by the key seat 7d and the key 12.

[0025] Then, the top end 10a of the projected rotating tool 10 is projected and moved predetermined quantity L1 in the direction as shown by the arrow A from the prior retracted position RP so as to position at a machining position MP. In this state, the top end 10a of the projected rotating tool 10 projects on the left hand in the figure rather than the top end 13b of the insert 13a of the cutting tool 13.

[0026] In this state, the tool holder 2 is rotated at a predetermined rotational number around the axial center CT by driving an appropriate driving unit of a tool rest, and the top end 10a of the projected rotating tool 10 is faced to the end face 15a of the workpiece 15. In this state, drilling/tapping machining (or milling machining) is performed on the end face 15a of the workpiece 15 with the projected rotating tool 10 being in a rotating state by moving the complex tool 1 in the direction as shown by the arrow A, that is, by relatively moving in the

workpiece 15 direction.

[0027] On this occasion, the top end 10a of the projected rotating tool 10 projects on the left hand in the figure rather than the top end 13b of the insert 13a of the cutting tool 13, as explained hereinbefore. Then, the machining with the projected rotating tool 10 can be smoothly performed without hindrance by the cutting tool 13 at the time of machining on the workpiece 15 with the projected rotating tool 10.

[0028] The above-mentioned embodiment refers to the case where the projected rotating tool 10 is provided being free to project in the axial center CT direction with respect to the tool holder 2. The projected rotating tool 10 is not always provided being free to project, but may be fixedly provided with respect to the main body 3 of the tool holder 2.

[0029] Besides, the projected rotating tool 10 may be a tool, such as a milling cutter, in addition to drill/tap as long as it is installed, corresponding the axial center CT which is a rotational center of the tool holder 2 and its axial center CT1 with each other, and rotating machining for machining a workpiece is performed by rotating the tool itself together with the tool holder 2.

[0030] The present invention is explained on the basis of the embodiments heretofore. The embodiments which are described in the present specification are illustrative and not limiting. The scope of the invention is designated by the accompanying claims and is not restricted by the descriptions of the specific embodiments. Accordingly, all the transformations and changes belonging to the claims are included in the scope of the present invention.

Claims

1. A complex tool to be used by attachably and detachably installing on a tool holding means, comprising:

a main body;
a tool means for turning provided at an outer periphery portion of said main body; and
a projected rotating tool means provided so as to correspond an axial center of said projected rotating tool means with an axial center of said main body; said complex tool having further character:

selectively performing turning machining with said tool means for turning or rotating machining for machining on a workpiece by rotating said projected rotating tool means.


2. The complex tool as set forth in claim 1 wherein said projected rotating tool means is fixedly provided in the axial center direction of said main body with respect to said main body.

3. The complex tool as set forth in claim 1 wherein said projected rotating tool means is provided so as to move in the axial center direction of said main body with respect to said main body.

4. The complex tool as set forth in claim 3 wherein a movement driving means of said projected rotating tool means is provided with the main body, and said movement driving means moves and drives said projected rotating tool means in the axial center direction by driving fluid supplied from said tool holding means side.

5. The complex tool as set forth in claim 1 wherein said projected rotating tool means is a drill, a tap, a milling cutter or an end mill.

Fig. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 11 8946

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 5 609 446 A (LINK HANS-JOERG ET AL) 11 March 1997 (1997-03-11) * the whole document *	1-5	B23B27/00 B23B51/00 B23C5/00
A	DE 37 33 298 A (FETTE WILHELM GMBH) 13 April 1989 (1989-04-13) * the whole document *	1	
A	EP 0 684 099 A (LINK JOHANN & ERNST GMBH & CO) 29 November 1995 (1995-11-29) * abstract; figures 1,2 *	1	
A	SU 1 722 793 A (MOGILEVSKIJ MASH) 30 March 1992 (1992-03-30) see english WPI abstract * abstract; figures *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B23B B23C
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 17 October 2001	Examiner Westhues, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02.92) (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 11 8946

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-10-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5609446	A	11-03-1997	DE 4421002 A1	21-12-1995
			DE 19528824 A1	06-02-1997
			DE 59508078 D1	04-05-2000
			EP 0687516 A1	20-12-1995
			JP 8057774 A	05-03-1996
DE 3733298	A	13-04-1989	DE 3733298 A1	13-04-1989
EP 0684099	A	29-11-1995	DE 4418571 A1	30-11-1995
			DE 59507675 D1	02-03-2000
			EP 0684099 A1	29-11-1995
SU 1722793	A	30-03-1992	SU 1722793 A1	30-03-1992

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82